

MASTER THE FIRE

"ENSURE FIRE SAFETY, SAVE LIFE AND SAVE PROPERTY"











MASTER THE FIRE



ABC STORED PRESSURE TYPE FIRE EXTINGUISHER

The **FIRE HUNT** ABC Dry Powder Extinguisher actually works on all types of Fire. Which posses every kind of risk factor. It is extremely versatile to tackle all risk of fire.

Features:

- Controlled Discharge
- Robust Design
- Powder as per IS 14609
- BIS Approved
- Good quality hose pipe
- **Quality Lining**

MODEL	FH-1	FH-2	FH-4	FH-6	FH-9
CAPACITY(KG)	1	2	4	6	9
ANTI-CORROSION INHIBITOR	Powder Coating	Powder Coating	Powder Coating	Powder Coating	Powder Coating
CONFIRMING IS CODE	15683	15683	15683	15683	15683
TYPE OF EXTINGUISHER	Store Pressure	Store Pressure	Store Pressure	Store Pressure	Store Pressure
TYPE OF EXTINGUISHER MEDIA	Dry Powder IS 14609	Dry Powder IS 14609	Dry Powder IS 14609	Dry Powder IS 14609	Dry Powder IS 14609
EXPELLANT	Pressurized N2 Gas	Pressurized N2 Gas	Pressurized N2 Gas	Pressurized N2 Gas	Pressurized N2 Gas
MINIMUM EFFECTIVE DISCHARGE (%)	85	85	85	85	85
MINIMUM JET LENGTH(M)	More than 2m	More than 2m	More than 2m	More than 2m	More than 2m
DISCHARGE TIME(SEC)	More than 13sec	More than 13sec	More than 13sec	More than 13sec	More than 13sec
HYDRAULIC TEST PRESSURE(KGF/CM²)	35	35	35	35	35
OPERATING POSITION	Upright	Upright	Upright	Upright	Upright
CHARGED PRESSURE (KGF/CM²)	15	15	15	15	15
OPERATING TEMPERATURE RANGE(°C)	-10 to +55°C	-10 to +55°C	-10 to +55°C	-10 to +55°C	-10 to +55°C
OPERATING VALVE	Squeeze grip type with Nozzle	Squeeze grip type with Nozzle	Squeeze grip type with Discharge Hose	Squeeze grip type with Discharge Hose	Squeeze grip type with Discharge Hose
FIRE RATING	1A, 8B	1A, 8B	2A, 21B	3A, 21B	4A, 34B

CLASSIFICATION OF FIRES



ORDINARY SOLID
MATERIAL FIRE



FLAMMABLE LIQUID FIRE



GAS VAPOUR FIRE



ELECTRICALLY INITIATED
FIRE



Manufactured by SPECTRA FIRE SYSTEMS PVT LTD DELHI

(AN ISO 9001:2015 CERTIFIED COMPANY)

Our Dealer/Distributor